

# WorldCup - Race

M1 WorldCup.1050.TQ SPITZING		M1 WorldCup.750.S <sub>Mag</sub> ERZBERG		M1 WorldCup.400.SX	
					
170 / 165mm & 29" / 27,5" 1050Wh TQ HPR 120S, 120Nm		170 / 160mm & 29" / 27,5" 750Wh Brose S <sub>Mag</sub> , 90Nm		170 / 170mm & 29" / 29" 400Wh + Opt. Range Ext. (250Wh) BOSCH SX, 55Nm	
25km/h Pedelec	45km/h S-Pedelec	25km/h Pedelec	45km/h S-Pedelec	25km/h Pedelec	
27,9 kg	28,5 kg	24,9 kg	25,6 kg	17,5 kg	

## Ausstattung / Specification

Größen / Framesize:	M , L		M , L		S/M , L , XL
Farbe / Colour:	GOLD		GREY		GREY
GABEL / fork	FOX 38 Factory, 170mm FIT4				FOX 36 Factory, 170mm FIT4
DÄMPFER / damper	FOX Float X Factory 230/65				FOX Float Factory 230/65
SCHALTUNG / shifter	Shimano XTR 12G (10-51)				
SATTELSTÜTZE / seatpost	FOX Transfer Factory 150mm				
LAUFRÄDER / wheels	Bike Ahead Composites BITURBO E				
KURBEL / crank	Carbon, FSA 165mm				
LENKER / handlebar	FSA Carbon GRADIANT, 800 mm				
VORBAU / stem	Reverse 35mm				
SATTEL / seat	Beast Components Grip Carbon Alcantara				
BREMSSCHEIBEN / brake disc	Shim.RT905 203mm	MDR-P 220/203	Shim.RT905 203mm	MDR-P 220/203	Shimano Rotor MT905 203mm
BREMSEN / brakes	Shimano SAINT	Magura MT5e	Shimano SAINT	Magura MT5e	Shimano XTR
KETTENBLATT / chain ring	42T	48T	36T	42T	32T
REIFEN / rims	EddyCurrent 2.6"	SmartSam 2.6"	EddyCurrent 2.6"	SmartSam 2.6"	NobbyNic 2.4"
MOTORSPANNUNG / voltage engine	48V		36V		36V
Rahmen, Unterfahrschutz / Frame, motorcover	Carbon, Carbon & downtube-rubber-cover		Carbon, Alu & downtube-rubber-cover		Carbon, Carbon & downtube-rubber-cover
SCHALTUNTERBRECHER / shift sensor	Gearsensor		-	Break CUT-OFF	-
APP	SIGMA EOX		Brose E-Bike App		BOSCH FLOW App
DISPLAY	SIGMA		Brose Allround		BOSCH Purion 200
LICHT / light	-	Lupine SL XS	-	Lupine SL XS	-
ENTNEHMBARER AKKU / removeable battery	yes		yes		yes
Steuerr. Länge & Winkel/ Headtube lenght & angle	(M)120 // (L)130 mm // 65°		(M) 120 // (L) 130 mm // 65°		(M)120 // (L)130 // (XL) 140 // 65,6°
Sattelrohr Länge & Winkel / Seattube lenght & angle	(M) 450 // (L) 500mm // 74°		(M) 450 // (L) 500mm // 74°		(M) 430 // (L) 470 // (XL) 510 // 75,2°